



SMARTSCOPE ZIP



Video and Multisensor Measurement for Large Parts

Field-Proven Performance For Large Part Measurement

	Travel	mm
ZIP 450	X axis	450
	Y axis	450
	Z axis	200
Extended Y (Option)	Y axis	610
Extended Z (Option)	Z axis	300

OGP® SmartScope ZIP® measurement systems are a popular choice in manufacturing facilities worldwide. These systems have a reputation for extreme reliability and proven metrological performance.

SmartScope ZIP 450 provides XYZ stage travel of 450x450x200 mm, with optional 610 mm Y-axis travel and 300 mm Z-axis travel. Traditionally strong in video measurement, ZIP 450 is also multisensor capable, and is available with contact and non-contact probes that deploy and retract under program control for fully automatic operation, as well as the unique switchable TTL laser.

- The patented AccuCentric® 5:1 auto-calibrating motorized zoom lens provides high quality images of virtually any part.
- DC servo motor drives provide accurate positioning control and high speed operation while the heavy duty metal and granite construction provides stability for accurate, repeatable metrology.
- Fast field-of-view (FOV) processing, autofocus, and MeasureMind® 3D MultiSensor metrology software with full 3D geometric functionality and multisensor support make measurement simple.
- Optional software extends utility, and includes contour fitting, and GD&T and SPC analysis.
- The granite-based bridge design combines the metrology benefits of rigid, orthogonal stage mounting with easy access for part fixturing.



Technical Specifications

■ Standard ■ Optional

<ul style="list-style-type: none"> ■ Stage travel (XYZ): 450 x 450 x 200 mm ■ Extended Y axis: 610 mm ■ Extended Z axis: 300 mm ■ Measuring unit dimensions (approx LWH): 138 x 102 x 168 cm, 1039 kg ■ XYZ scale resolution: 0.1 μm ■ Motor drives: DC servo ■ Interactive stage control: 4 axis (X,Y,Z,zoom) with ergonomic, multi-function handheld controller ■ Stage velocity: Z axis min 100 mm/sec; X,Y axis 250 mm/sec ■ Worktable: Hardened worktable with fixture holes, removable stage glass, and 75 kg load capacity
<ul style="list-style-type: none"> ■ Zoom lens: Patented[†] 5:1, AccuCentric[®] auto-calibrating, motorized, 10 position ■ Lens attachments: 0.5x, 0.75x, 1.5x, 2.0x ■ Front replacement lenses: 2.0x, 2.5x, 5.0x, 10.0x ■ Adapter tubes: 1.0x 0.67x, 2.0x ■ Illumination: Substage LED backlight (collimated, green), white TTL LED surface illumination, and patented^{††} SmartRing[™] white LED illuminator Vu-Light oblique illuminator, small fiber optic ring light, fiber optic surface light, large fiber optic ring light ■ Camera: ½" format high resolution color CCD with 768 x 494 pixel array High resolution black and white (in lieu of color camera) ■ Image processing: 256 level grayscale processing with 10:1 sub-pixel resolution ■ Multisensor options: Touch probe and change rack, DRS[™] laser, TTL laser, Rainbow Probe[™] scanning white light sensor, Feather Probe[™], laser pointer (not available with TTL laser) (contact OGP for possible combinations of sensors)
<ul style="list-style-type: none"> ■ Power requirements: 115/230 vac, 50/60 Hz, 1 φ, 900 W ■ Rated environment: Temperature between 18 and 22° C, stable to ± 1° C; 30-80% humidity (non-condensing); vibration <0.001g below 15 Hz ■ Operating environment, safe operation: 15-30° C
<ul style="list-style-type: none"> ■ Computer: Minimum configuration Dual Core processor @ 1.8 GHz, 1.0 GB RAM, 80 GB hard drive, 1.44 MB floppy drive, DVD-RW drive, parallel, serial, and USB 2.0 ports, on board 10/100 LAN ■ Operating system: Microsoft[®] Windows[™] XP Professional ■ Computer accessory package: 22" flat panel LCD monitor, or dual 22" flat panel LCD monitors, keyboard, mouse (or user supplied) ■ Metrology software: OGP MeasureMind[®] 3D MultiSensor OGP Measure-X[®] (in lieu of MeasureMind 3D), MeasureMind 3D offline ■ Software: For use with Measure-X or MeasureMind 3D; MeasureFit[®] Plus, MeasureMenu[™], SmartReport[®] powered by QC-Calc[™], Scan-X[®] ■ Software: For use with MeasureMind 3D only; SmartFit[®] 3D, SmartScript[®], SmartTree[™], SmartProfile[™]
<p>Where L=measuring length in mm. Applies to thermally stable system in rated environment. All optical accuracy specifications at maximum zoom lens setting.</p> <ul style="list-style-type: none"> ■ XYZ volumetric accuracy: $E_3 = (2.8 + 6L/1000) \mu\text{m}^*$ ■ XY area accuracy: $E_2 = (1.8 + 4L/1000) \mu\text{m}^{**}$ ■ Z linear accuracy: $E_1 = (2.5 + 5L/1000) \mu\text{m}^{***}$ ■ Z linear accuracy: $E_1 = (2.0 + 5L/1000) \mu\text{m}^{***}$ (with optional 2.0x replacement lens/grid projector) ■ Z linear accuracy: $E_1 = (1.5 + 5L/1000) \mu\text{m}^{***}$ (with optional TTL laser, or DRS-2000 laser) ■ Z linear accuracy: $E_1 = (1.0 + 5L/1000) \mu\text{m}^{***}$ (with optional DRS-300 or -500 laser, or TP-20 or -200 touch probe)
<ul style="list-style-type: none"> ■ Warranty: One year ■ Accessories: Calibration artifacts, rotary indexers

[†]Patent Number 5,389,774 ^{††}Patent Number 5,690,417

*XYZ volumetric artifact: QVI dual linear grid reticle.

**With evenly distributed 5 kg load in the standard measuring plane. Depending on load distribution, accuracy at maximum rated load may be less than standard accuracy. XY axis artifact: QVI 25 intersection grid reticle in the standard measuring plane. The standard measuring plane is defined as a plane that is 25 mm above the worktable.

***Z axis artifact: QVI step gage or master gage blocks.



Multisensor Measurements for Manufacturing Professionals

World Headquarters and Technology Center: 850 Hudson Avenue • Rochester, NY 14621 USA • Tel 585.544.0400 • Fax 585.544.8092

Western USA Regional Office: 615 South Madison Drive • Tempe, AZ 85281 USA • Tel 480.889.9056 • Fax 480.889.9059

OGP Shanghai Co, Ltd: 17 Lane 593 • East Jin An Rd • Pu Dong New District • Shanghai, China 201204 • Tel 86.21.5045.8383/8989 • Fax 86.21.6845.8800

OGP Messtechnik GmbH: Nassaustr. 11 • 65719 Hofheim-Wallau, Germany • Tel 49.6122.9968.0 • Fax 49.6122.9968.20

Optical Gaging (S) Pte Ltd: 21 Tannery Road, 347733 Singapore • Tel 65.67.41.8880 • Fax 65.6846.8998

Internet: www.ogpnet.com • intl-sales@ogpnet.com